

**strautmann**

Stall manure spreader BE 4 / BE 6

- Solid chassis design
- Milled chain wheels made of high-tensile steel
- Low loading height for easy loading
- High spreading precision for all spreading materials
- Thick-walled auger blades with wide-angle spreading tines
- Quick removal of the spreading unit ensures flexible use



Perfection to the last detail is the outstanding feature of the Strautmann spreaders BE 4 and BE 6

Due to decades of experience in spreader manufacturing and to the high quality awareness, the Strautmann stall manure spreaders have proven extremely well in practice. Whether equipped with 2 or 4 drums, both spreading units are extremely robust and guarantee high spreading precision. Powder-coated side walls with screwed-on side wall protection strips protect against corrosion and damage.

Data	Typ	BE 4	BE 6
total weight max.	kg	5800	7500
with tandem axle		--	8000
Tare weight	kg	ca. 1600	ca. 1920
Dimensions overall	LxWxH	6,45 x 2,19 x 2,30	6,75 x 2,19 x 2,38
Box internal dimensions	LxWxH	4,15 x 1,80 x 0,50	4,45 x 1,80 x 0,90
Capacity	m ³	8,0	9,4
Power requirement from	KW/HP	20/28	33/45
Tyres		11,5/80-15,3 (10 PR)	12,5/80-18 (12 PR)
Track	mm	1650	1650

All diagrams, technical data and weights are subject to change by way of ongoing technical development of our products and are therefore not binding for delivery.