

**strautmann**

Easy distribution of silage Fodder distribution trailer

- Scraper floor continuously adjustable, operated from the tractor seat.
- As an option, continuous speed adjustment for variable discharge width.
- Hydraulically driven scraper floor with high-strength round steel chains of 13 mm size.



Reliable, low-cost and efficient serving of basic fodder for all sizes of farms.

Robust and low-main-tenance vehicles meet the requirements of agricultural practice. A cross conveyor with left- and right-handed rotation or a split cross conveyor on request ensure a regular fodder discharge without any blocking.

Data	Typ	100/100 H	120/120 H	140/140 H	160/160 H
Max weight	kg	6900	7800	8000	8000
Max supporting load	kg	1000	1250	1000	1250
Capacity	m ³	10	12	14	16
caste Dimensions (L x W x H)	m	4,4 x 1,8 x 1,2	5,2 x 1,8 x 1,2	4,4 x 1,8 x 1,7	5,2 x 1,8 x 1,7
Length					
- Conveyor front	m	6,50	7,30	6,50	7,30
- Conveyor rear	m	6,70	7,50	6,70	7,50
overall width	m	2,30	2,30	2,30	2,30
overall height	m	2,32	2,45	2,95	2,95
Power requirement from	KW/HP	30/40	37/50	37/50	37/50
H = Conveyor rear					

All diagrams, technical data and weights are subject to change by way of ongoing technical development of our products and are therefore not binding for delivery.