

**strautmann**

Silo block cutter Hydrofox HK^{Plus}

- Quick silage removal
- Clean cutting surface
- With lift frame, as an option
- Cutters driven via power block
- Permanently tight tines due to conic tine mounting
- Control valves disk-type design for trouble-free extension



Hydrofox HK^{Plus} for an even quicker and cleaner removal of silage.

Due to an additionally integrated advance control system that adapts itself automatically to the silage hardness, a higher cutting speed is achieved for maize and grass silage. A machine's own hydraulic system ensures the advance of the cutting arm even in hardest silage independently of the hydraulic performance of the tractor. So the Hydrofox HK^{Plus} handles even hard and dry silage without any problems. Due to the trapezoid outline of the cutting arm, the silage bales are cleanly removed without any corners breaking off the silo stock.

Data	TYP	HK-1	HK-2	HK-3	HK-4
Bale size	DxWxH	0,83 x 1,80 x 1,16	0,83 x 1,80 x 1,46	0,83 x 1,80 x 1,66	0,83 x 1,80 x 1,86
Capacity	m ³	1,75	2,20	2,50	2,80
Power requirement from	kW/HP	35/45	45/60	60/80	65/90
basic Tare weight	kg	475	500	530	550

All diagrams, technical data and weights are subject to change by way of ongoing technical development of our products and are therefore not binding for delivery.