



Removal and distribution Siloblitz

- Replaceable wearing runners
- Hydraulic operation of all functions
- Fodder discharge on the right or on the left, as desired
- Metering unit for regular discharge
- Removal, transport and distribution of silage by means of one machine



The Siloblitz is a machine for removing silage and distributing it on the feeding table.

These machines have been especially developed for small- and medium-sized farms that do not want to use a fodder mixing trailer yet. The Siloblitz models are coupled via three-point linkage or to the tractor linkage drawbar. Their compact design ensures maximum manoeuvrability especially in narrow and low stables.

Data	Typ	210 KD	250 KD	250 KA	330 KA
overall width					
- Conveyor R or L	m	2,14	2,14	2,18	2,24
- Conveyor R and L	m	2,36	2,36	2,36	2,36
overall width on removal					
- Conveyor R or L	m	2,50	2,50	2,54	2,60
- Conveyor R and L	m	2,72	2,72	2,72	2,72
Removal height	m	3,30	3,70	3,50	3,43
Capacity	m ³	2,10	2,40	2,40	3,30
Tare weight					
- Conveyor R or L	kg	960	1100	1245	1700
- Conveyor R and L	kg	1030	1170	1310	1770
with scraper plate		Series	Series	Series	Series
Tyres 21 x 8 -9		--	Series	Series	--
Tyres 175 R 14 C		--	--	--	Series

K =with scraper plate A =machines are wheel operated D =machines operate in 3-point linkage

All diagrams, technical data and weights are subject to change by way of ongoing technical development of our products and are therefore not binding for delivery.