



Short-cut silage trailer Super Vitesse

- Cutting unit with 37 knives
- Spring-loaded tandem bogie axle
- Extremely robust and low-maintenance feeding unit
- Hydraulic articulated drawbar with double-acting cylinders
- Pick-up with a width of 1.80 m with 5 tine rows and standard guide roller
- Two-sided torsion-free drive of the loading rotor via solid duplex chains



With the Super-Vitesse series Strautmann offers a robust high-performance forage trailer for farmers and contractors.

In practical use, the high productive capacity of this forage trailer can be made full use of. The robust feeding unit and an uncontrolled, low-maintenance and low-wear loading rotor has proven to be decisive for the high performance and efficiency of the Super-Vitesse.

Data	Typ	SV I	SV II	SV II-H	SV III	SV I DO	SV II DO	SV II-H DO	SV III DO
Tandem axle		Series	Series	Series	Series	Series	Series	Series	Series
Dimensions									
Length	m	7,85	8,55	8,55	9,35	8,60	9,30	9,30	10,10
Width	m	2,37	2,37	2,37	2,37	2,45	2,45	2,45	2,45
Height	m	3,65	3,65	3,82	3,82	3,65	3,65	3,82	3,82
true capacity DIN 11741 (Series)	m ³	25,0	28,0	28,0	32,0	25,0	28,0	28,0	32,0
capacity w. unloaded mat. (Series)	m ³	45,5	51,0	51,0	56,0	45,5	51,0	51,0	56,0
permissible total weight (Series)	kg	8000	8000	15000	15000	8000	8000	15000	15000
permissible total weight (Optional)	kg	12000	12000	-	-	12000	12000	-	-
2 Dosage unit		-	-	-	-	Series	Series	Series	Series
3 Dosage unit		-	-	-	-	optional	optional	optional	optional
Knives		37	37	37	37	37	37	37	37
loading rotor unit width	m	1,80	1,80	1,80	1,80	1,80	1,80	1,80	1,80
Series Tyres		19.0/45-17 (10 PR)	19.0/45-17 (10 PR)	500/55-20 (12 PR)	500/55-20 (12 PR)	19.0/45-17 (10 PR)	19.0/45-17 (10 PR)	500/55-20 (12 PR)	500/55-20 (12 PR)
Power requirement from	KW HP	66 90	74 100	74 100	88 120	66 90	74 100	74 100	88 120

All diagrams, technical data and weights are subject to change by way of ongoing technical development of our products and are therefore not binding for delivery.